

Amendments

Amendments to the Claims:

Please amend the claims as set forth below.

1. (Currently Amended) A support structure comprising:
 - a pair of side rails, each comprising an upper portion, a middle portion, and a lower portion;
said portions corresponding to each other on the respective pair of side rails;
 - a pair of cross-bars connecting said pair of side rails and crossing each other at a location between at least one of said lower portions, said middle portions and said upper portions of said side rails, said pair of cross-bars being extensions of said pair of side rails and forming an X-shape in crossing each other, wherein each one of said pair of cross-bars extends from its respective side rail to the other respective side rail; and
 - a plurality of transverse wires extending between said pair of side rails, wherein said pair of cross-bars have an average bending stiffness greater than at least one of said transverse wires.
2. (Original) The support structure as in claim 1 wherein said pair of cross-bars are fixedly attached to said pair of side rails with clips.
3. (Cancelled)
4. (Original) The support structure as in claim 1 wherein said pair of cross-bars incorporate angled portions.
5. (Original) The support structure as in claim 1 wherein said transverse wires incorporate angled portions.
6. (Original) The support structure as in claim 1 wherein said transverse wires are wound around said side rails to fixedly attach.

7. (Original) The support structure as in claim 1, further comprising a seat frame, wherein said support structure is suspended in said seat frame.
8. (Original) The support structure as in claim 1 wherein one or a plurality of said transverse wires extend laterally beyond said side rails after having been wound around said wires.
9. (Original) The support structure as in claim 8, further comprising a seat frame wherein one or a plurality of said transverse wires extending beyond said side rails connects to said seat frame.
10. (Currently Amended) The support structure as in claim 1 wherein one or a plurality of ~~links~~brackets are fixedly attached to said side rails.
11. (Currently Amended) The support structure as in claim 10 further comprising a seat frame wherein one or a plurality of said ~~links~~brackets fixedly attach to said seat frame.
12. (Original) The support structure as in claim 1, further comprising a central longitudinal cord, said central longitudinal cord is fixedly attached to the mid points of said transverse wires.
13. (Currently Amended) The support structure as in claim 1, further comprising an adjusting mechanism~~actuator assembly~~ operatively connected to said side rails.
14. (Original) The support structure as in claim 1, further comprising a pair of brackets, wherein one of said brackets is fixedly attached to one of said side rails.
15. (Original) The support structure as in claim 14, further comprising a pair of Bowden cables; wherein each of said Bowden cables has a first end and a second end and each of said first ends are slidably inserted through one of said brackets.
16. (Original) The support structure as in claim 15, further comprising an actuator, wherein said second ends of said Bowden cables are fixedly attached to said actuator.

17. (Currently Amended) The support structure as in claim 1, wherein the average bending stiffness of all of said pair of cross-bars is greater than the average bending stiffness of said transverse wires.

18. (Cancelled)

19. (Original) The support structure as in claim 1, wherein said pair of cross-bars are extensions of at least one of said upper portion and lower portion of said side rails.

20. (Previously Presented) A support structure comprising:

a first side rail and a second side rail, each comprising a first portion and a second portion;

a first cross-bar connecting said first portion of said first side rail to said second portion of said second side rail;

a second cross-bar connecting said first portion of said second side rail to said second portion of said first side rail;

a plurality of transverse wires extending between said pair of side rails, wherein an average bending stiffness of at least one of said first cross-bar and said second cross-bar is greater than at least one of said transverse wires.

21. (Original) The support structure as in claim 20 wherein said first cross bar and said second cross-bar are fixedly attached to said first side rail and said second side rail with clips.

22. (Cancelled)

23. (Original) The support structure as in claim 22 wherein said transverse wires incorporate angled portions.

24. (Original) The support structure as in claim 20 wherein said first cross bar and said second cross bar incorporate angled portions.

25. (Original) The support structure as in claim 20 wherein said transverse wires are wound around said first side rail and said second side rail to fixedly attach.
26. (Original) The support structure as in claim 20, further comprising a seat frame, wherein said support structure is suspended in said seat frame.
27. (Original) The support structure as in claim 20 wherein one or a plurality of said transverse wires extend laterally beyond said first side rail and said second side rail after having been wound around said first side rail and said second side rail.
28. (Original) The support structure as in claim 27, further comprising a seat frame wherein one or a plurality of said transverse wires extending beyond said first side rail and said second side rail connects to said seat frame.
29. (Currently Amended) The support structure as in claim 20 wherein one or a plurality of links~~brackets~~ are fixedly attached to said first side rail and said second side rail.
30. (Currently Amended) The support structure as in claim 29 further comprising a seat frame wherein one or a plurality of said links~~brackets~~ fixedly attach to said seat frame.
31. (Original) The support structure as in claim 20, further comprising a central longitudinal cord, said central longitudinal cord is fixedly attached to the mid points of said transverse wires.
32. (Currently Amended) The support structure as in claim 20, further comprising an adjusting mechanism~~actuator assembly~~ operatively connected to said first side rail and said second side rail.
33. (Original) The support structure as in claim 20, further comprising a pair of brackets, wherein one of said brackets is fixedly attached to one of said first side rail and said second side rail.

34. (Original) The support structure as in claim 33, further comprising a pair of Bowden cables; wherein each of said Bowden cables has a first end and a second end and each of said first ends are slidably inserted through one of said brackets.

35. (Original) The support structure as in claim 34, further comprising an actuator, wherein said second ends of said Bowden cables are fixedly attached to said actuator.

36. (Currently Amended) The support structure as in claim 20, wherein the average bending stiffness of said first cross-bar and said second cross-bar is greater than the average bending stiffness of all of said transverse wires.

37. (Cancelled)

38. (Original) The support structure as in claim 20, wherein said first cross-bar and said second cross are extensions of one of said first portion and said second portion of one of said first side rail and second side rail.

39. (Currently Amended) A support structure comprising:

a pair of side rails, wherein each of said side rails ~~has~~have a first end and a second end, ~~and~~wherein said second ends of said side rails are angled and wherein each of said second ends extends from one of said pair of side rails and is fixedly attached to said~~an~~ opposite one of said pair of side rails~~lateral wire~~ to form an X-shape;

a plurality of transverse wires, said transverse wires having first and second ends wherein one of said ends is fixedly attached to one of said side rails and the other said end is fixedly attached to other said side rail;

a central longitudinal cord, said central longitudinal cord is fixedly attached to the mid points of said transverse wires;

a pair of brackets, wherein one of said brackets is fixedly attached to one of said side rails;

a pair of Bowden cables; wherein each of said Bowden cables has a first end and a second end and each of said first ends are slidably inserted through one of said brackets; and

an actuator, wherein said second ends of said Bowden cables are fixedly attached to said actuator.

40. (Original) The support structure as in claim 39, wherein said second ends of said side rails are fixedly attached to other said side rail with clips.

41. (Cancelled)

42. (Original) The support structure as in claim 39 wherein said transverse wires incorporate angled portions.

43. (Original) The support structure as in claim 39 wherein said pair of side rails incorporate angled portions.

44. (Original) The support structure as in claim 39 wherein said transverse wires are wound around said pair of side rails to fixedly attach.

45. (Original) The support structure as in claim 39, further comprising a seat frame, wherein said support structure is suspended in said seat frame.

46. (Original) The support structure as in claim 39 wherein one or a plurality of said transverse wires extend laterally beyond said pair of side rails after having been wound around said pair of side rails.

47. (Original) The support structure as in claim 46, further comprising a seat frame wherein one or a plurality of said transverse wires extending beyond said pair of side rails is fixedly connected to said seat frame.

48. (Currently Amended) The support structure as in claim 39 wherein one or a plurality of ~~links~~brackets are fixedly attached to said pair of side rails.

49. (Currently Amended) The support structure as in claim 48 further comprising a seat frame wherein one or a plurality of said ~~links~~brackets are fixedly attached to said seat frame.

50. (Original) The support structure as in claim 39, wherein the average bending stiffness of said transverse wires is less than the average bending stiffness of said pair of side rails.

51. (Cancelled)

52. (Currently Amended) A support structure comprising:

a pair of side rails, each having an upper portion, a middle portion, and a lower portion;

a pair of cross bars in an X shape extending between and fixedly attached to said side rails;

and

a plurality of transverse wires extending between said pair of side rails wherein said pair of cross bars have~~has~~ an average bending stiffness greater than at least one of said transverse wires.